

**CORRIGENDUM No. 1**

**Sub: Modernization of MDRC Health Club – 1st Floor including Civil, Electrical, HVAC, including Gymnasium, Furniture Works, Lifts and Structural Works at MDL, Mumbai**

**Ref: Tender No. 180000028 dated 13 Dec' 16**

The following points shall be considered by the bidder(s) before submission of final offer for the subject tender.

<b>Item No. of TEF Vol-III</b>	<b>Item Description</b>	<b>Page No.</b>	<b>Additional Description (To be added in respective item description)</b>
25	Providing and fixing in position 40mm thick solid core water proof marine grade flush door shutters with marine ply as per IS: 710(water proof quality) 40mm thick and T.W. lipping 40mmx12mm with T.W. beading (Architrave) 6mmx40mm to teakwood frames including hinges,stopper,SS handle,mortice lock,door closure, & 4mm thick veneer with melamine polish on one side & 1.5mm thick approved laminate on other side etc. complete as directed. (Type D12) (Location - Store room)	6 of Vol-III	Basic rate of veneer Rs.2000/sq.mt Basic rate of laminate Rs.645/sq.mt
26	Providing & fixing in position 38 mm thk solid core approved brand flush door, finished with 1.5 mm thk. Laminate of approved pattern from bothside,38X12mm T W beading all around the shutter, and with steel plate at bottom inclusive of heavy duty brass hinges of 100 x 25mm along with approved make cylindrical lock, S. S. finish Handles-300mm, S. S. finish Tower bolt-200mm, door stopper, door closure, etc as per approval and complete all as per drg.,details and as directed.all complete & as directed by Engineer / Architect (Type D4, D10 & D11)(Location-Toilet/Pantry/Childrens party area)	7 of Vol-III	<b>Please find attached Annexure A for product details.</b>
27	Providing & fixing in position 38 mm thk solid core approved brand flush door, finished with 1.5 mm thk. Laminate of approved pattern from bothside,38X12mm T W beading all around the shutter, including cutting for vision panel & teakwood frame 12X38mm with melamine polish & 8mm thick toughened glass , and with steel plate at bottom inclusive of heavy duty brass hinges of 100 x 25mm along with approved make cylindrical lock, S. S. finish Handles-300mm, S. S. finish Tower bolt-200mm, door stopper,door closure, etc as per approval and complete all as per drg.,details and as directed.all complete & as directed by Engineer / Architect. (Type D07) (Location- Toilet main entrance)	7 of Vol-III	<b>Please find attached Annexure A for product details.</b>
28	Providing & fixing in position 38 mm thk solid core approved brand flush door, finished with 1.5 mm thk. Laminate of approved pattern	7 of Vol-III	<b>Please find attached Annexure A for product details.</b>



	from bothside,38X12mm T W beading all around the shutter, and with steel plate at bottom ,cylindrical lock, S. S. finish Handles-300mm, S. S. finish Tower bolt-200mm, door stopper,door closure, panic handle on inside etc as per approval and complete all as per drg.,details and as directed.all complete & as directed by Engineer / Architect. (location - Ground floor entrance)		
29	Providing & fixing in position 38 mm thk solid core approved brand flush door, finished with 1.5 mm thk. Laminate of approved pattern from both side,38X12mm T W beading all around the shutter, and with steel plate at bottom inclusive of heavy duty brass hinges of 100 x 25mm along with approved make cylindrical lock, S. S. finish Handles-300mm, S. S. finish Tower bolt-200mm, door stopper,lock,pivot fixture, floor spring, vision panel etc as per approval and complete all as per drg.,details and as directed.all complete & as directed by Engineer / Architect. (Type D09) (Location- Fire escape staircase)	7 of Vol-III	<b>Please find attached Annexure A for product details.</b>
30	Providing and fixing Double/single swing fully Glazed Door Shutters with 12mm thick toughened glass fixed on patch fittings of approved make and as per design and details given by the architect/ including locking arrangement, handles 350mm long, accessories, floor spring make "Dorma" BTS 84/75/approved equivalent as per door weight complete as directed. (Type D1,D2, & D3) (Location - Lift lobby/childrens party area/gym)	7 of Vol-III	<b>Please find attached Annexure A for product details.</b>
31	Providing and fixing Double/single swing fully Glazed shutter with 12mm thick bronze tinted tempered glass on patch fittings with stainless steel spring hinges & weather seal around the door, wooden handle 200mm long, warpage resistant jambs, & ball catches etc. complete etc. complete as per drawing. (Type 06) (Location - Steam room)	8 of Vol-III	<b>Please find attached Annexure A for product details.</b>
32	Providing and fixing full height Openable anodized glazed aluminium doors as per details and specifications mentioned in the drawing, size 1200X2400mm, using 160X 25mm anodized aluminium box section finished with PVDF of approved shade & type for subframes, frames, shutter frames mullions, couplers, tubular sections, beadings etc. from approved manufacturers including shutter with clear glass of 12 m thick of approved make, & commercially available fixtures, holdfasts, fixing by drilling in concrete (if required) concealed handles,locks, Neoprene gaskets for fixing glass and	8 of Vol-III	<b>Please find attached Annexure A for product details.</b>



	anodizing all aluminium sections to a thickness of anodic film not less than 20 microns (or powder coated) and sealing all the joints with approved make silicon sealant etc. complete as directed. (Type DR13) (Ground floor lift lobby entrance)		
34	Providing and fixing 12/18mm thick compact cubicle door of Merino/Greenlam make including SS 316 - 12mm box, SS 304 latch box & indicator, SS 304 door knob, SS 304 hinges with cover, SS 304 coar hook RG, rubber strip for groove, SS 304 top rail, SS privacy thumbturn, SS 316 adjustable foot, SS 'U' channel etc. complete. As per manufacturer specifications. (Type D5) (For Toilet)	8 of Vol-III	Make- 1. Merino Titan Standard Series 2. Greenlam Classique Evergreen
35	Providing and fixing 12/18mm thick compact cubicle partition of Merino/Greenlam make including SS 316 - 12mm box, SS 304 latch box & indicator, SS 304 hinges with cover, SS 304 coar hook RG, rubber strip for groove, SS 304 top rail, SS privacy thumbturn, SS 316 adjustable foot, SS 'U' channel etc. complete. As per manufacturer specifications. (For Toilet)	8 of Vol-III	Make- 1. Merino Titan Standard Series 2. Greenlam Classique Evergreen
36	Providing and fixing GRC cornice fixed as per manufacturer specification & as per drawing. Sizes are following etc. complete-350mm wide & 600mm ht.	8 of Vol-III	Contact details of Vendors for reference if required are as under. However, the bidder is free to get the material from any other vendor Sudarshana - ECOEARTH SOLUTIONS OPC PVT LTD Mob : 9167492486
37	Providing and fixing GRC cornice fixed as per manufacturer specification & as per drawing. Sizes are following etc. complete-185mm wide & 300mm ht	8 of Vol-III	Contact details of Vendors for reference if required are as under. However, the bidder is free to get the material from any other vendor GRC INDIA CO SRIHARI NILKAR 9867569395
38	Providing and fixing GRC cornice fixed as per manufacturer specification & as per drawing. Sizes are following etc. complete-120mm & 150mm ht	8 of Vol-III	Contact details of Vendors for reference if required are as under. However, the bidder is free to get the material from any other vendor Mr. Sukesh Singh - (+91 9820464366) M/s COMPOSITE MOULDINGS.
39	Providing and fixing GRC cornice fixed as per manufacturer specification & as per drawing. Sizes are following etc. complete-300mm & 600mm ht	8 of Vol-III	Contact details of Vendors for reference if required are as under. However, the bidder is free to get the material from any other vendor Mr. Sukesh Singh - (+91 9820464366) M/s COMPOSITE MOULDINGS.



40	Providing and fixing GRC cornice fixed as per manufacturer specification & as per drawing. Sizes are following etc. complete-75mm & 150mm ht	8 of Vol-III	Contact details of Vendors for reference if required are as under. However, the bidder is free to get the material from any other vendor Mr. Sukesh Singh – (+91 9820464366) M/s COMPOSITE MOULDINGS.
41	Providing and fixing approved veneer/mirror panelling with 25X40mm aluminium box section @ 600X600mm C/C @ horizontal & vertically, 8mm thick marine plywood fixed on aluminium framework, mirror panelling consisting 6mm thick mirror of approved make, & veneer panelling consisting of 8mm thick marine plywood with 4mm thick veneer, & aluminium "L"/"T" angle fixed between the veneer & mirror panelling. including two coats of melamine polish to the veneer all hardware etc. complete as per drawing or as directed.	9 of Vol-III	Basic rate for Veneer Rs.2000 /sq.mt
42	Providing and fixing approved veneer panelling with 25X40mm aluminium box section @ 600X600mm C/C @ horizontal & vertically, veneer panelling consisting of 12mm thick marine plywood with 4mm thick veneer, including two coats of melamine polish to the veneer all hardware etc. complete as per drawing or as directed.	9 of Vol-III	Basic price for Veneer Rs. 2000 /SQ.MT
43	Providing and fixing approved panelling with 35X35mm Teakwood framework @ 600X600mm C/C @ horizontal & vertically, veneer panelling consisting of 19mm thick marine plywood with 8mm thick Corian on top , including polishing to the teakwood framework & all hardware etc. complete as per drawing or as directed.	9 of Vol-III	Basic price for Corian Rs. 800-850 /SQ.MT
43	Providing and fixing approved panelling with 35X35mm Teakwood framework @ 600X600mm C/C @ horizontal & vertically, veneer panelling consisting of 19mm thick marine plywood with 8mm thick Corian on top , including polishing to the teakwood framework & all hardware etc. complete as per drawing or as directed.	9 of Vol-III	Basic rate for Veneer Rs.2000 /sq.mt
49	Providing and fixing 5000 X 2320X100 mm thick acoustic movable wall partition system, 52Db Rw, individually movable panels, suspended from a top track only, each panel to have top and bottom operable pressure seals operated by a crank handle through double scissor mechanism with pressure compensation spring of 2000N for an optimal strength. The elements must be interconnected by means of a positive locking concave/convex aluminium profile integrated with magnetic profile having a linear attraction of 40 N/m. Elements must be	10 of Vol-III	Make-DOORS & DOORS, DORMA



	<p>constructed of a non-deflecting steel tube frame and aluminium profiles, bolted together. The frame must be clad either side with 16 mm MDF panels hung in acoustic isolation from the frame and allowed to vibrate independently of the frame. The fascia panels must also be easily removable. The panel must be filled with high density rock wool in accordance with the specified sound insulation requirements. The telescopic element must open and close 120 mm and must be operated by a single mechanism for both the top and bottom seals.</p> <p>a) Including spindle/jack &amp; gear mechanism &amp; acoustic material. Internal mild steel sturdy frame consisting of 45X45X3mm hollow tubing with steel reinforcements. End panel fitted with interlocking aluminium profile duly fitted with 4 polarised magnetic strips.</p> <p>b) Each panel laid on with MDF boards of 16mm thick, width of each panel 974mm with single suspension guide trolleys/per panel, total panel 5nos including 1 telescopic panel.</p> <p>c) Providing and fixing sound baffle above sliding/folding partition to the required profile and shape, including steel work, track suspension hardware, sonic &amp; sound baffle for above the false ceiling area, specifications and as per directions of Engineer-in-charge.</p>		
54	Providing and applying Epoxy Zinc Phosphate Paint 2 coats 35 microns each PLUS 2 coats of PU paint for aesthetical finish.	12 of Vol-III	Basic rate Rs.15/kg
55	Providing and applying Fire Protection Coat : Single Coat of Epoxy Paint (Primer) 35 microns PLUS Vermiculite Spray for 120 minutes Fire rating.	12 of Vol-III	Basic rate Rs.25/kg
56	Providing and applying One coat of zinc rich primer after properly cleaning the steel surface with wire brush and mild acid solution followed by washing with water and drying the surface completely.	12 of Vol-III	Basic rate Rs.15 /kg
62	Providing and laying Crazy ceramic tile flooring, with under layer 12 mm thick cement mortar 1:4 (1 cement: 4 coarse sand), with joints not exceeding 5 mm, including filling the gaps with ordinary cement mixture & mixing with synthetic polyester fibre, triangular in shape having specific gravity of 1.34 to 1.40, cross section size ranging from 10 to 40 micron & length upto 6 mm, mixing fibre @ 125 grams per 50 kg of cement in cement mortar, including providing and mixing water proofing material in mortar @ 1 kg per 50 kg of cement, all complete as per direction of Engineer-in-charge.	13 of Vol-III	Basic price for crazy ceramic tiles Rs. 400 /SQ.MT



70	Providing and fixing Wet cladding of size 1000 X 3000 X 3mm thick Techlam porcelain sheet with matt & slip resistant finish, Techlam tile fixed with adhesive of MapaeiKeraflexi maxi s1, latcrete, kerakol or equivalent make. 2mm joints finished with epoxy grout of Mapaei or latcrete make, etc. complete as per manufacturer specifications.	14 of Vol-III	Basic rate Rs. 300-350 /SQ.FT
73	Providing and fixing 60mm thick flagstone of approved size, colour, & make characteristic bending strength >4MPa, abrasion resistance-class I as per EN 1339:2003, <18000mm <sup>2</sup> /5000mm <sup>2</sup> including 50mm thick sand bedding and compacting with plate vibrator, filling the gaps etc. complete as per manufacturer specifications.	15 of Vol-III	Basic rate of flagstone Rs. 500 /SQ.MT Make- Vyara, Basant Batons, Supertiles & Marbles, Hindustan Block Manufacturers.
74	Providing and fixing 15mm thick rubberised flooring of Nora, Sandick make, fixed on concrete with approved adhesive, as per manufacturer specifications etc. complete as per design or as directed.	15 of Vol-III	Basic rate of rubberised flooring Rs. 2100 /SQ.MT
80	<b>KALZIP ROOFING:</b> a) The roofing system manufacturers shall be certified with UnderWriter Laboratories (UL-90) for wind uplift & ISO Certificate (ISO 9001) . Installer to submit the above alongwith the Offer. B) Installer must submit Certificate from manufacturer as authorised installer of the roofing system. c) Installer must submit Certificate from manufacturer as authorised installer of the roofing system. And must submit list of such similar Aluminum standing seam roofs for minimum 5 projects in India having roof area more than 3,000 m <sup>2</sup> each. d) Installer should submit necessary documents, like photographs & completion certificates, TDS certificate of the earlier projects as proof for qualification. e) Installer should offer a 15 years warranty for material and leakage warranty of 10 years. f) Installer must have carried out aluminium welding for openings in aluminium standing seam roofing systems and should submit photographs & certificate as a proof of expertise. g) Installer should submit all detailed drawings required for the project. h) Installer to submit certificates of training from the Manufacturer's training facility for its key personnel in - Project execution, Quality,	16-17 of Vol-III	Contact details of Vendors for reference if required are as under. However, the bidder is free to get the material from any other vendor.  1. VIJAYNATH SHETTY - Mob.: +91 - 9821015336 (KINGSPAN) 2. ABHISHEK GUPTA - Mob : 9987681976 (KALZIP )



<p>Design &amp; General management. KingZip SF (KINGSPAN / BEMO / SANKYO) ALUMINIUM DOUBLE SKIN INSULATED ROOFING SYSTEM Note for 71.1: Supply and fixing of KingZip SF, 65/400 Self Supported Secret Fix ROOFING SYSTEM in 0.9 mm thick in Marine Grade AA 3004 Aluminium Alloy comprising of the following layers: 1.Top Layer - The topmost profiled sheeting of aluminium KingZip SF 65/400 self supported roof system manufactured from Aluminium alloy AlMnMg1 Quality AA 3004, in accordance with B209M/ BS-EN-485-2:1995 minimum material thickness of 0.90mm with 60µm Durobond finish in accordance with BS-EN-1396: 2007 finish including Accessories. Colour as per Architect's choice. The profile should have Architectural micro ribs between every 24 mini ribs of 1.5 mm to provide additional strength at the pan. The support halters shall be manufactured from extruded aluminium alloy 6082 T6 in accordance with BSEN 755 part 2. Each aluminium halter shall be coupled with a 6mm thick black polyamide thermal barrier base pad. The material properties shall be as follows: Ultimate tensile strength: minimum 200 N/mm<sup>2</sup>, 0.2% Proof Stress: min 185 N/mm<sup>2</sup>, Modulus of elasticity: 70,000 N/mm<sup>2</sup>. KingZip SF to be laid in Single Length to meet the requirements of the building geometry (straight sheet) and fixed on Aluminium Clip/ Halter and which is fixed to steel top hat through with SS-304 screws. 1) Detail structural load calculation report to be submitted by the manufacturer based on wind load as per IS 875 and screw pull out force. Approved Makes : KINGSPAN / BEMO / SANKYO 2. Insulation Layer - Rockwool Insulation of 100 mm thickness x 60kg/m<sup>3</sup> density. K-value 0.038 W/mK as per standard ASTM C-518. Fire classification as per BS 476: Part 6&amp;7 / EN-1350-1 / UL-273. MAKE- ROXUL / ROCKWOOL 3. Vapour Control Layer - Double sided aluminium foil with 170 microns thickness. 4. Bottom Sheet - Supply &amp; Fixing of bare Galvalume profile sheet of 1000-1015 mm effective cover width and 28-35 mm height ribs with subtle square fluting in the five pan at 200-250 mm centre-to-centre. The feed material is manufactured out of nominal 0.47 mm Total Coated Thickness (TMT), Hi-strength steel with min. 550 MPa yield</p>		
--	--	--



	strength, metallic hot dip coated with Aluminium-Zinc alloy (55% Aluminium, 45% Zinc) as per AS 1397 - Zinalume/ Galvalume (Make- Tata bluescope / Jindal) AZ150 (Min. 150 gms/sq.mt total on both sides) Fixed to the purlins with steel screws (Make- Buildex / Corroshiled) at 500mm spacing.		
82	<p>Providing and fixing in position UV resistant X-structure/multiwall/multicell Polycarbonate sheet (Lexan Thermoclear of GE Plastics or equivalent 1200 mm width and max length upto 12.0 m, including UV resistant coating on both sides, providing specially designed serrated polycarbonate clamping section at all longitudinal joints (parallel to span) on supporting member, fixing to box purlins/runner using specially designed stainless steel clamps and fasteners SS304 grade,(or) specially designed anodised aluminium clamping section with EPDM/Neoprene gaskets to be located on supporting member, the fasteners to be fixed on pre drilled or self drilled hole, all fixing to be completely water tight. The Contractor shall give 20 years guarantee for Polycarbonate sheets against deterioration and discolouration, loss of light transmission, loss of strength due to weathering, and 10 years guarantee for leakage across laps, fasteners, joints etc. Contractor shall submit detail shop drawings showing the layout of sheets, fixing arrangement, joint details for approval prior to procurement. a) 16 mm thk X-structure/multiwall/multicell (X-structure to be LT2UV 16/3 x 2.9 of GE Plastics or equivalent) (Purlin/Runners are paid separately under structural steel item)</p>	18 of Vol-III	Polycarbonate sheet to be put at site for existing steel staircase which shall be as per manufacturer's specifications. For better understanding, a site visit is recommended.
84	<p>Designing for specified spans as shown in structural drawings as a composite floor (deck sheet of min. thickness 1 mm ) for the design loads mentioned herein, providing, delivering at site, cutting to required size, laying, installing, securing to floor beams with appropriate shear connectors / studs, laying reinforcement if required, propping if necessary before concreting (concrete and reinforcement item paid separately under Concrete tender) etc. complete. (Material conforming to EN 10147:2000 or AS 1397 with minimum yield strength of <math>F_y = 300</math> N/sqmm. Galvanization to be min. zinc coating mass of 275 gm/sqmm or as per ASTM A653)</p>	18 of Vol-III	Basic rate Rs.1500 /SQ.MT





97	Providing and filling styrofill geofoam of approved size etc. complete as per manufacturer specifications.	20 of Vol-III	Contact details of Vendors for reference if required are as under. However, the bidder is free to get geofoam item from any other vendor True Pack Thermo Products - 9920764666 2mtr x 1mt x 250mm - RS.2000
100	Providing and applying Oikos or equivalent make internal textured paint of approved shade and colour etc. complete.	20 of Vol-III	Basic rate Rs. 2000 /SQ.MT
135	Providing & installing self watering planter boxes of size (upto 500 X 500mm and upto 470mm high) of high density fibre & LECHUZA make etc. complete as directed.	24 of Vol-III	Contact details of Vendors for reference if required are as under. However, the bidder is free to get self watering planter box from any other vendor Gaia Pottery - 9920144085 Ratanshi's plant nursery - 022-2372 329
137	Providing and fixing LUXALON Aluminium perforated (2mm),84C Ceiling system. Providing & fixing Luxalon 84C aluminium panel, ceiling manufactured by M/S. Hunter Douglas India Pvt. Ltd. approved colour consisting of panel 84mm wide X 15.5mm deep X0.5mm with square edges & recess flange of 24mm , panel length upto 6m, coil coated on continous paint line, double backed and roll formed from enamelled corrosion resistance aluminium alloy AA5050 (Al.Mg) for higher strength and good roll forming characteristics. Panel shall be clipped to baked enamelled aluminium panel carrier 62mm wideX29mmdeepX0.9mm thick etc. complete as per manufacturer specifications.	25 of Vol-III	Basic rate Rs 4500 /sq.mt
186	Providing and installing reception table as shown in drawing of 825 and 2350mm high in 25mm thick marine plywood/35mm water proof faced flush board for top with 8mm thick corian,19mm marine plywood , key board trays, finished with 1.5mm thick laminate to all exposed outer faces,including 8mm thick Corian fixed on top of size 1740X300 & 750X500mm, wire manager, including pedestal with 19mm thick marine plywood finished with 1.5mm thick laminate on external surface & 1mm thick for internal surface etc. complete or as directed. Reception table of size 2350 mm x 825 mm	30 of Vol-III	Basic rate RS 7500/8000 sq.mt
188	Providing & installing Coffee/side table of size 1000x600X428mm with teakwood base of size 50X50mm, at bottom 12mm thick marine plywood finished with veneer with melamine polish & teakwood lipping, 10mm thick	30 of Vol-III	Basic rate Rs. 20,323 per unit



	approved glass on top with 50X25mm teakwood frame around the glass, Rubber bushes at the legs bottom etc. as per design and details and as directed. (Make Godrej)		
189	Providing and installing Zella 4 seater Dining table set 1) Dining table 1050mm X 1050mm X 750mm Ht., Teakwood legs support of size 100X100mm with 25mm thick marine plywood finished with 4mm thick veneer with melamine polish with teakwood edge banding etc. complete as per drawing. Make - URBAN LADDER. 2) Supplying and fixing dining chairs - 4nos of size 475X450X450/990mm high with 12mm thick marine plywood on base, leg support with teakwood of size 50X40mm, Back with 50X12mm teakwood frame & 12X12mm X 5nos. Slates, 50mm thick cushion on seat etc. complete as per drawing. Make - URBAN LADDER	30 of Vol-III	Basic rate Rs. 31000 /set.
190	Supplying chairs with proper ergonomic design,synchrotilt mechanism,multi position tilt lock,pneumatic gas mechanism for height adjustment, m.s. metal base with powder coating,fixed type polypropelene arm rests,the metal connector joining the back and the seat to be of m.s.strip of size not less than 5mm X 52mm, m.s. tubular powder coated pipe back upholstered with high quality net fabric, seat made of 10mm hot pressed ply or PU with moulded foam, nylon base and nylon castors, all welding should be continuous fillet weld (spot welding should be avoided) to avoid unstable seat etc. (Durian/BP Ergo/Godrej make)	31 of Vol-III	Basic rate Rs.5000 per unit
191	Supplying and fixing Parsons wooden sofa set of size 1790X770X490/740mm high with teakwood framework & 75mm thick cushion for back & 100mm thick cushion on seat etc. complete as per drawing. (Make - Urban Ladder) (i) Two seater sofa	31 of Vol-III	Basic rate Rs. 50000 /set.
192-210	Gym Work (Gym Equipment)	31-33 of Vol-III	Contact details of Vendors for reference if required are as under. However, the bidder is free to get Gym Equipments from any other vendor Preeti Pandey Marwah- General Manager-Sales- Gympac Fitness Systems P Ltd - 9967662246



2. The basic rate indicated in the items in the BOQ in TEF Vol-III & Corrigendum-I are inclusive of VAT on material.
3. With reference to working time restrictions refer Cl. No: 07 Pg no: 08 of Procedure for Issue of Entry Pass at our website [www.mazdock.com](http://www.mazdock.com) ---> Tenders ---> Infra-Projects ---> STACS/Format and refer clause no: 11.2 of Tender Enquiry Form Vol-II
4. The closing date of the Tender is extended to **1 Feb' 2017 at 1430 hrs** and Opening date of the Tender extended to **3 Feb' 2017 at 1430 hrs.**
5. All other terms & conditions remain unaltered.
6. The Corrigendum-I as above, duly signed & stamped, shall be scanned and submitted along with Techno-commercial Bid (PART-I) of the offer.

**Signature of Contractor**

**Seal**

**Date**